

KDC-1044 低速离心机

Low speed centrifuge



特性:

- ★ 微电脑控制、LCD 液晶显示
- ★ 交流变频电机驱动，运行宁静清洁
- ★ 提供 9 种升、降速率选择模式；提供 10 种工作模式选择，可自由编程、调用
- ★ 转速 / 离心力可相互设定、同步显示
- ★ 两种计时模式可选：运行开始计时和到达设定转速开始计时，切换方便
- ★ 门盖双挂杆设计、磁感应门锁，电动开门，运行更加安全可靠
- ★ 离心偏重容忍度最大可达 30 克，无需专门称重配平
- ★ 运行中可随时更改参数，无需停机
- ★ 独特的风冷排风设计，温升高、噪音小。

Features:

- ★ Microcomputer control, LCD liquid crystal display(LCD).
- ★ Ac frequency conversion motor drive, quiet operation clean.
- ★ Offers nine ascending and descending rate selection mode; Offer ten kinds of working mode selection ,can free programming call.
- ★ Speed/centrifugal force can be set and double synchronous display screen.
- ★ Two optional timing mode: run start timing and timing starts to set speed, easy to switch.
- ★ Door with double lock rod design, magnetic locks, electric door, more safety and reliable operation.
- ★ Centrifugal lay particular stress on tolerance up to 30 grams, no special load balancing.
- ★ Can change at any time in the operation of the parameters without downtime
- ★ Unique design of air exhaust temperature, low noise.

KDC-1044 可选配的转头、提篮

| 序号 | 转头、吊杯 | 最高转速 (rpm) | 最大离心力 (×g) | 主机 |
|------|-------|------------|------------|--------------------|
| NO.1 | 水平转头 | 4500 | 3387 | 4 × 600ml (圆吊杯) |
| 1 | 提篮 | 4200 | 3387 | 16 × 50ml |
| 2 | 提篮 | | | 76 × 10ml |
| 3 | 提篮 | | | 96 × 真空采血管 |
| 4 | 提篮 | | | 4 × 250ml |
| 5 | 提篮 | | | 12 × 100ml |
| 6 | 提篮 | | | 40 × 15ml (尖底带盖) |
| 7 | 提篮 | | | 148 × 5ml (放免管) |
| NO.2 | 水平转头 | 4500 | 3321 | 148 × 真空采血管 (蜂窝吊杯) |

KDC-1044 技术指标

| | |
|----------------------|--------------------------------------|
| 最高转速Max speed | 4200rpm |
| 最大相对离心力Max RCF | 3387 × g |
| 转速精度Speed accuracy | ± 10rpm |
| 转子最大容量Rotor capacity | 600ml × 4 |
| 温升指标Temperature rise | ≤10℃ (运行20分钟) |
| 噪音Noise | ≤55dB |
| 定时范围Timer range | 1min ~ 99:99:59 (hh:mm:ss) / 连续/短时离心 |
| 结构Construction | 钢制结构，不锈钢离心腔 |
| 重量Weight | 90kg |
| 外形尺寸Dimensions | 580 × 740 × 520mm (L × W × H) |