

性能参数	型号 SX ₂ -2.5-10TZ SX ₃ -4-10TZ SX ₃ -4-10TBZ SX ₃ -8-10TZ SX ₃ -8-10TBZ SX ₃ -12-10TZ SX ₃ -16-10TZ SX ₃ -2.5-12TZ SX ₃ -4-12TZ SX ₃ -4-12TBZ SX ₃ -10-12TZ SX ₃ -10-12TBZ SX ₃ -12-12TZ SX ₃ -16-12TZ SX ₃ -4-13TZ SX ₃ -6-13TZ SX ₃ -8-13TZ																			
	加热元件	镍铬丝																		
加热元件														硅碳棒						
容积/功率 电压	2 2.5 220	7.2 4 220	12 4 220	16 8 380	36 8 380	30 12 380	36 8 380	2 2.5 220	7.2 4 220	12 4 220	16 10 380	30 12 380	36 10 380	80 16 380	220 220 380	380 380 380	380 380 380	220 220 380	380 380 380	18 8 380
控温范围/ 最高温度	RT+30~1000													RT+30~1300						
升温速率/ 波动度	900													1100	1200					
	20~30													30~50						
	±2																			
外形尺寸	560	640	670	690	740	760	860	860	560	640	670	690	740	760	860	860	575	575	800	800
	670	770	770	885	890	985	990	670	770	770	885	890	985	985	990	985	785	785	930	930
	845	905	965	945	1075	985	1185	845	905	965	945	1075	985	985	1185	830	830	1065	1065	
工作室 尺寸	120	200	200	250	300	300	400	120	200	200	250	300	300	400	400	150	150	250	250	
	200	300	300	400	400	500	500	200	300	300	400	400	500	500	500	300	300	400	400	
	80	120	200	160	300	200	400	80	120	200	160	300	200	400	400	100	100	150	150	
货运信息	61	86	96	110	132	130	179	61	86	96	110	132	130	179	179	91	91	161	161	
	50	68	78	92	110	107	138	50	68	78	92	110	107	138	138	71	71	128	128	
	570x690	650x780	680x810	700x900	750x930	780x995	870x1020	570x690	650x780	680x810	700x900	750x930	780x995	870x1020	630x800	800x930	800x930	800x930	800x930	
	x820	x900	x930	x930	x1050	x965	x1170	x820	x900	x930	x930	x930	x965	x1050	x870	x870	x1060	x1060		

外包装尺寸(长x宽x高),尺寸长度为设备的左右尺寸,宽度为设备前后尺寸,本公司随时保留更改技术参数的权利